A1263L10Q320741CZ

Welding environment
Q32

Technical data :	
Rated operating distance (Sn)	7 mm
Mounting mode	Flush
Output type	PNP
Function	NO
Operating voltage	10…30 V DC
Operating current	200 mA
No-load consumption	< 10 mA
Voltage drop	< 2 V
Residual current	< 70 µA
Ambient temperature range	-25...70 °C
Hysteresis	3...15 %
Repeatability	< 5 %
Switching frequency	600 Hz
Protection :	
Reverse polarity protection	
Short-circuit protection	
Overload protection	
IEC 61000-4-2 (ESD)	4 kV contact / 8kV air
IEC 61000-4-4 (Burst)	2kV / 5kHz
IEC 61000-4-6 (RF conducted)	3V 150kHz…80MHz
Protection degree	IP67
Materials :	
Housing	Anodized aluminium
Sensing face	Ceramic
Status indication :	
Power	Green LED
Output	Yellow LED
Connection :	
Connector	M12
Cable	PVC
Cable length	1 m (0/+30 mm)
Cable protection	Silicone-coated fiberglass braided sleeving

CE RoHS

Dimensions :





Connection diagram :



Pin assignment :



For uses in particularly harsh environments: Please enquire
We reserve the right to modify all or part of characteristics of our products without warning.

Printed on: 12 nov. 2015