

### Technical data :

|                           |             |
|---------------------------|-------------|
| Rated voltage             | 60 V AC/DC  |
| Rated current             | 4 A         |
| Insulation resistance     | > 1000 MΩ   |
| Ambient temperature range | -25...70 °C |

### Protection :

|                   |      |
|-------------------|------|
| Protection degree | IP67 |
|-------------------|------|

### M8 straight female connector :

|                            |  |
|----------------------------|--|
| Locking nut/screw material | CuZn, nickel-plated                          |
| Overmoulding material      | TPU, self-extinguishing                      |
| Contact diameter           | Ø1 mm  |
| Contact material           | CuZn, pre-plated with nickel and gold-plated |
| Contact resistance         | < 5 mΩ                                       |

### Cable characteristics :

|                               |                              |
|-------------------------------|------------------------------|
| Sheath material               | PVC                          |
| Wire structure                | 3 x 0,34 mm <sup>2</sup>     |
| Conductor class               | 6                            |
| Sheath diameter               | 5 mm                         |
| Flame resistance according to | IEC 60332-1 (VDE 0472-804/B) |
| Oil resistance according to   | CNOMO E03.40.150.N           |

### Cable length :

|              |            |
|--------------|------------|
| L length     | 2 m        |
| Other length | On request |

### Accessories (included) :


1 label holder

## L8V/3L25

Industrial automation



### Dimensions :



### Wiring diagram :

