


| Technical data : | |
|--------------------------------|--|
| Rated voltage | 30 V AC/DC |
| Rated current | 4 A |
| Insulation resistance | > 1000 MΩ |
| Ambient temperature range | -25...70 °C |
| Protection : | |
| Protection degree | IP67 |
| M8 straight male connector : | |
| Locking nut/screw material | CuZn, nickel-plated |
| Overmoulding material | TPU, self-extinguishing |
| Contact diameter | Ø1 mm |
| Contact material | CuZn, pre-plated with nickel and gold-plated |
| Contact resistance | < 5 mΩ |
| M8 straight female connector : | |
| Locking nut/screw material | CuZn, nickel-plated |
| Overmoulding material | TPU, self-extinguishing |
| Contact diameter | Ø1 mm |
| Contact material | CuZn, pre-plated with nickel and gold-plated |
| Contact resistance | < 5 mΩ |
| Cable characteristics : | |
| Sheath material | PVC |
| Wire structure | 4 x 0,34 mm ² |
| Conductor class | 5 |
| Sheath diameter | 5 mm |
| Flame resistance according to | IEC 60332-1 (VDE 0472-804/B) |
| Cable length : | |
| L length | 3 m |
| Other length | On request |
| Accessories (included) : | |
| 2 label holders | |

L8V/4MLL31R

Industrial automation



Dimensions :



Wiring diagram :

