

### Technical data :

Rated voltage	48 V AC/DC
Rated current	4 A
Insulation resistance	> 1000 MΩ
Ambient temperature range	-25...70°C

### Protection :

Protection degree	IP67
-------------------	------

### M12 straight male connector :

Locking nut/screw material	Zamak, nickel-plated
Overmoulding material	TPU, self-extinguishing
Contact diameter	Ø1 mm
Contact material	CuZn, pre-plated with nickel and gold-plated
Contact resistance	< 5 mΩ

### M12 straight female connector :

Locking nut/screw material	Zamak, nickel-plated
Overmoulding material	TPU, self-extinguishing
Contact diameter	Ø1 mm
Contact material	CuZn, pre-plated with nickel and gold-plated
Contact resistance	< 5 mΩ

### Cable characteristics :

Sheath material	Halogen free PUR
Wire structure	4 x 0,34 mm <sup>2</sup>
Conductor class	6
Sheath diameter	5,3 mm
Cable construction according to	UL-AWM Style 20549/10493
Halogen free cable according to	DIN VDE 0472 Part 815
Cable silicone free and LABS free according to	PV 3.10.7
Flame resistance according to	UL FT2
Oil resistance according to	UL 758
Admissible torsion	+/- 360 °/ m
Drag chain suitable	
Minimum static bending radius :	5 x Ø
Minimum dynamic bending radius :	10 x Ø
Resistant to weld splatters	

### Cable length :

L length	15 m
Other length	On request

### Accessories (included) :


2 label holders

## S12/4MLL154VG

Suitable for welding application



### Dimensions :



### Wiring diagram :

