

**Technical data :**

Operating voltage	60 V DC
Rated current	4 A
Insulation resistance	> 1000 MΩ
Ambient temperature range	-25...70°C

**Protection :**

Protection degree	IP67
-------------------	------

**M12 straight male connector :**

Locking nut/screw material	Zamak, nickel-plated
Overmoulding material	TPU, self-extinguishing
Contact diameter	Ø1 mm
Contact material	CuZn, pre-plated with nickel and gold-plated
Contact resistance	< 5 mΩ

**M12 straight female connector :**

Locking nut/screw material	Zamak, nickel-plated
Overmoulding material	TPU, self-extinguishing
Contact diameter	Ø1 mm
Contact material	CuZn, pre-plated with nickel and gold-plated
Contact resistance	< 5 mΩ

**Cable characteristics :**

Sheath material	Halogen free PUR
Wire structure	5 x 0,34 mm <sup>2</sup>
Conductor class	6
Sheath diameter	6,9 mm
Flame resistance according to	IEC 60332-1
Oil resistance according to	EN 50363 & IEC 60811-2-1
Halogen free cable according to VDE 0472, part 815	

**Cable length :**

L length	0,4 m
Other length	On request

**Accessories (included) :**


2 label holders

## S12/5MLL0042W

Press tools



**Dimensions :**



**Wiring diagram :**

